

Revision nr. 1

Dated 02/02/2024 First compilation Printed on 02/02/2024

Style Oltre

Page n. 1/14

Safety Data Sheet

According to Annex II to REACH - Regulation (EU) 2020/878 and to Annex II to UK REACH

SECTION 1. Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

455650 Code: Style Oltre Product name

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified Uses Consumer Industrial Professional

Smoothing compound for floors and walls

Uses Advised Against

All uses other than application on walls and floors in construction

1.3. Details of the supplier of the safety data sheet

Full address Via IV Novembre, 4 55016 Porcari (LU) District and Country

Italia

Tel. 199.11.99.55 Fax 199.11.99.77

CROMOLOGY ITALIA S.P.A.

e-mail address of the competent person

responsible for the Safety Data Sheet info-sds@cromology.it

1.4. Emergency telephone number

For urgent inquiries refer to Contact your local poison control centre.

For more information: Cromology Italia SpA Phone +39 05832424

from Monday to Friday 9:30-12:30 14:00-17:30

SECTION 2. Hazards identification

2.1. Classification of the substance or mixture

The product is classified as hazardous pursuant to the provisions set forth in (EC) Regulation 1272/2008 (CLP) (and subsequent amendments and supplements). The product thus requires a safety datasheet that complies with the provisions of (EU) Regulation 2020/878. Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

Hazard classification and indication:

H317 Skin sensitization, category 1A May cause an allergic skin reaction.

2.2. Label elements



Revision nr. 1

Dated 02/02/2024
First compilation
Printed on 02/02/2024

Style Oltre

Page n. 2/14

Hazard labelling pursuant to EC Regulation 1272/2008 (CLP) and subsequent amendments and supplements.

Hazard pictograms:



Signal words: Warning

Hazard statements:

H317 May cause an allergic skin reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P280 Wear protective gloves.

P302+P352 IF ON SKIN: Wash with plenty of water and soap.

P333+P313 If skin irritation or rash occurs: Get medical advice / attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container according to local regulation.

Contains: REACTION MASS OF: BIS (1,2,2,6,6-Pentamethyl-4-Piperidyl) Sebacate and Methyl 1,2,2,6,6-Pentamethyl-4-Piperidyl

Sebacate

1,2-BENZOISOTIAZOL-3(2H)-ONE (BIT)

2.3. Other hazards

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

The product does not contain substances with endocrine disrupting properties in concentration ≥ 0.1%.

SECTION 3. Composition/information on ingredients

3.2. Mixtures

Contains:

Identification x = Conc. % Classification (EC) 1272/2008 (CLP)



Revision nr. 1

Dated 02/02/2024
First compilation

Printed on 02/02/2024

Page n. 3/14

Style Oltre

REACTION MASS OF: BIS (1,2,2,6,6-Pentamethyl-4-Piperidyl) Sebacate and Methyl 1,2,2,6,6-Pentamethyl-4-Piperidyl Sebacate

 $0.2 \le x < 0.25$

Repr. 2 H361f, Skin Sens. 1A H317, Aquatic Acute 1 H400 M=1, Aquatic

Chronic 1 H410 M=1

EC 915-687-0

EC 220-120-9

CAS 1065336-91-5

REACH Reg. 01-2119491304-40-

XXXX

INDEX

1,2-BENZOISOTIAZOL-3(2H)-ONE

(BIT)

INDEX 613-088-00-6 $0 \le x < 0.05$

Acute Tox. 4 H302, Eye Dam. 1 H318, Skin Irrit. 2 H315, Skin Sens. 1A H317,

Aquatic Acute 1 H400 M=1, Aquatic Chronic 2 H411

Skin Sens. 1A H317: ≥ 0,05%

CAS 2634-33-5 LD50 Oral: 532 mg/kg

REACH Reg. 01-2120761540-60

The full wording of hazard (H) phrases is given in section 16 of the sheet.

Contains titanium dioxide, Cas n. 13463-67-7 (containing <1 % of particles with aerodynamic diameter ≤ 10 µm, therefore not classified in the car. 2, H351). However, for reasons of precaution, the product was classified EUH211: attention! In case of vaporization, dangerous breathing droplets can form. Do not breathe the vapors or mists

SECTION 4. First aid measures

4.1. Description of first aid measures

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 15 minutes, opening the eyelids fully. If problem persists, seek medical advice.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention immediately. Wash contaminated clothing before using it again.

INHALATION: Remove to open air. If the subject stops breathing, administer artificial respiration. Get medical advice/attention immediately. INGESTION: Get medical advice/attention immediately. Do not induce vomiting. Do not administer anything not explicitly authorised by a doctor.

4.2. Most important symptoms and effects, both acute and delayed

Information not available

4.3. Indication of any immediate medical attention and special treatment needed

Information not available

SECTION 5. Firefighting measures

5.1. Extinguishing media

SUITABLE EXTINGUISHING EQUIPMENT

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray. UNSUITABLE EXTINGUISHING EQUIPMENT None in particular.

5.2. Special hazards arising from the substance or mixture

HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE



Do not breathe combustion products.

5.3. Advice for firefighters

GENERAL INFORMATION

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

SECTION 6. Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

SECTION 7. Handling and storage

7.1. Precautions for safe handling

Before handling the product, consult all the other sections of this material safety data sheet. Avoid leakage of the product into the environment. Do not eat, drink or smoke during use. Remove any contaminated clothes and personal protective equipment before entering places in which people eat.

7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store the containers sealed, in a well ventilated place, away from direct sunlight. Keep containers away from any incompatible materials, see section 10 for details.

7.3. Specific end use(s)

Information not available

SECTION 8. Exposure controls/personal protection



Style Oltre

| Revision | nr. | 1 |
|----------|-----|---|
| | | |

Dated 02/02/2024
First compilation

Printed on 02/02/2024

Page n. 5/14

8.1. Control parameters

| REACTION MASS OF: BIS (1,2,2,6,6-Pentamethyl-4-Pip Predicted no-effect concentration - PNEC | eridyl) Sebacate and Methyl 1,2,2, | 6,6-Pentamethyl-4-Piperidyl Sebacate |
|--|------------------------------------|--------------------------------------|
| Normal value in fresh water | 0,0022 | mg/l |
| Normal value in marine water | 0,00022 | mg/l |
| Normal value for fresh water sediment | 1,05 | mg/kg |
| Normal value for marine water sediment | 0,11 | mg/kg |
| Normal value for water, intermittent release | 0,009 | mg/l |
| Normal value of STP microorganisms | 1 | mg/l |
| Normal value for the terrestrial compartment | 0.21 | ma/ka |

| Health - Derived no-eff | ect level - DNEL / D | MEL | | | | | | |
|-------------------------|----------------------|----------------|---------------|------------------|-------------|----------------|---------------|------------------|
| | Effects on | | | | Effects on | | | |
| | consumers | | | | workers | | | |
| Route of exposure | Acute local | Acute systemic | Chronic local | Chronic systemic | Acute local | Acute systemic | Chronic local | Chronic systemic |
| Oral | | | | 0,18 mg/kg/d | | | | |
| Inhalation | | | | 0,31 mg/m3 | | | | 1,27 mg/m3 |
| Skin | | • | • | 0,9 mg/kg/d | • | | | 1,8 mg/kg/d |

VND = hazard identified but no DNEL/PNEC available ; NEA = no exposure expected ; NPI = no hazard identified ; LOW = low hazard ; MED = medium hazard ; HIGH = high hazard.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration.

When choosing personal protective equipment, ask your chemical substance supplier for advice.

Personal protective equipment must be CE marked, showing that it complies with applicable standards.

Provide an emergency shower with face and eye wash station.

HAND PROTECTION

Protect hands with chemical resistant gloves (EN 374).

In the case of mixtures, the resistance of work gloves to chemical agents must be checked before use as it is not always predictable.

Materials also suitable for direct and prolonged contact, it is recommended: protection factor 6,> 480 minutes of permeation time (EN 374); neoprene, nitrile rubber and others. Additional information: Information is based on our experience, bibliographic data and information from glove manufacturers, or derived from substances / mixtures of similar composition. The duration of use of a protective glove can be influenced by various factors such as temperature and therefore in practice significantly lower than the permeation time detected by the test.

Due to the great variety of types, it is advisable to observe the instructions for use of the glove manufacturers.

SKIN PROTECTION

Wear category II professional long-sleeved overalls and safety footwear (see Regulation 2016/425 and standard EN ISO 20344). Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (see standard EN 166).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, use a mask with a type A filter whose class (1, 2 or 3) must be chosen according to the limit of use concentration. (see standard EN 14387). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.

Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold



Revision nr. 1

Dated 02/02/2024 First compilation Printed on 02/02/2024

Style Oltre

Page n. 6/14

values considered. The protection provided by masks is in any case limited.

If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus (in compliance with standard EN 137) or external air-intake breathing apparatus (in compliance with standard EN 138). For a correct choice of respiratory protection device, see standard EN 529.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

SECTION 9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

| Properties Appearance | Value liquid | Information |
|---|--------------------------|---|
| Colour | white, various | |
| Odour | not available | |
| Melting point / freezing point Initial boiling point | < 5 °C not available | Method:Derived |
| Flammability | not flammable | |
| Lower explosive limit | not available | |
| Upper explosive limit | not available | |
| Flash point Auto-ignition temperature | > 60 °C not available | Method:Derived |
| Decomposition temperature | not available | |
| Нд | 9,5 | Method:ISO 19396-1 Temperature: 20 °C |
| Kinematic viscosity | not available | Reason for missing data:Not significant data for classification |
| Dynamic viscosity | 15000-20000 mPa.s | Method:ISO 2884-1 Temperature: 20 °C |
| Solubility | not available | |
| Partition coefficient: n-octanol/water | not available | |
| Vapour pressure | not available | |
| Density and/or relative density | 1,8 kg/l | Method:ISO 2811-1 Temperature: 20 °C |
| Relative vapour density | not available | |
| Particle characteristics | not applicable | |
| | | |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Information not available

9.2.2. Other safety characteristics

Information not available



Style Oltre

Revision nr. 1

Dated 02/02/2024
First compilation

Printed on 02/02/2024

Page n. 7/14

SECTION 10. Stability and reactivity

10.1. Reactivity

There are no particular risks of reaction with other substances in normal conditions of use.

10.2. Chemical stability

The product is stable in normal conditions of use and storage.

10.3. Possibility of hazardous reactions

No hazardous reactions are foreseeable in normal conditions of use and storage.

10.4. Conditions to avoid

None in particular. However the usual precautions used for chemical products should be respected.

10.5. Incompatible materials

Information not available

10.6. Hazardous decomposition products

In the event of thermal decomposition or fire, gases and vapours that are potentially dangerous to health may be released.

SECTION 11. Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available



Revision nr. 1

Dated 02/02/2024
First compilation
Printed on 02/02/2024

Style Oltre

Page n. 8/14

| ı | Interactive | affacts |
|---|---------------|---------|
| ı | IIILEI ALLIVE | enecis |

Information not available

ACUTE TOXICITY

ATE (Inhalation) of the mixture:

ATE (Oral) of the mixture:

Not classified (no significant component)

Not classified (no significant component)

ATE (Dermal) of the mixture:

Not classified (no significant component)

1,2-BENZOISOTIAZOL-3(2H)-ONE (BIT)

LD50 (Oral): 532 mg/kg LC50 (Inhalation mists/powders): 0,4 mg/l/4h

CALCIUM CARBONATE

LD50 (Oral): 6450 mg/kg Rat

Titanium dioxide (content <1% of particles with aerodynamic diameter ≤ 10 μm)

LD50 (Oral): > 5000 mg/kg Rat, Method 425 OECD

REACTION MASS OF: BIS (1,2,2,6,6-Pentamethyl-4-Piperidyl) Sebacate and Methyl 1,2,2,6,6-Pentamethyl-4-Piperidyl Sebacate

LD50 (Oral): > 3230 mg/kg rat OECD 401

SKIN CORROSION / IRRITATION

Does not meet the classification criteria for this hazard class

SERIOUS EYE DAMAGE / IRRITATION

Does not meet the classification criteria for this hazard class

RESPIRATORY OR SKIN SENSITISATION

Sensitising for the skin

GERM CELL MUTAGENICITY



Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

Contains titanium dioxide, Cas n. 13463-67-7 (containing <1 % of particles with aerodynamic diameter ≤ 10 µm, therefore not classified in the car. 2, H351). However, for reasons of precaution, the product was classified EUH211: attention! In case of vaporization, dangerous breathing droplets can form. Do not breathe the vapors or mists

REPRODUCTIVE TOXICITY

Does not meet the classification criteria for this hazard class

STOT - SINGLE EXPOSURE

Does not meet the classification criteria for this hazard class

STOT - REPEATED EXPOSURE

Does not meet the classification criteria for this hazard class

ASPIRATION HAZARD

Does not meet the classification criteria for this hazard class

11.2. Information on other hazards

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with human health effects under evaluation.

SECTION 12. Ecological information

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

12.1. Toxicity

1,2-BENZOISOTIAZOL-3(2H)-ONE (BIT)



Revision nr. 1

Dated 02/02/2024 First compilation Printed on 02/02/2024

Style Oltre

Page n. 10/14

LC50 - for Fish 11 mg/l/96h Oncorhynchus mykiss (OECD 203)

EC50 - for Crustacea 16,4 mg/l/48h Daphnia magna (OECD 202)

EC50 - for Algae / Aquatic Plants 0,6 mg/l/72h Selenastrum capricornutum (OECD 201)

Titanium dioxide (content <1% of particles with aerodynamic diameter ≤ 10 µm)

> 1000 mg/l/96h LC50 - for Fish

EC50 - for Crustacea > 100 mg/l/48h Test Method 202 OECD

REACTION MASS OF: BIS (1,2,2,6,6-Pentamethyl-4-Piperidyl) Sebacate and Methyl 1,2,2,6,6-Pentamethyl-4-Piperidyl

Sebacate

EC50 - for Algae / Aquatic Plants 1,68 mg/l/72h

Chronic NOEC for Crustacea 1 mg/l 21 days, Daphnia magna

12.2. Persistence and degradability

Titanium dioxide (content <1% of particles with aerodynamic diameter ≤ 10 µm)

Solubility in water < 0,001 mg/l

Degradability: information not available

12.3. Bioaccumulative potential

1,2-BENZOISOTIAZOL-3(2H)-ONE (BIT)

Partition coefficient: n-octanol/water 0,7 n-Octanol/Water, OECD 117

BCF 6,95 Pesce (OECD 305)

12.4. Mobility in soil

Information not available

12.5. Results of PBT and vPvB assessment

On the basis of available data, the product does not contain any PBT or vPvB in percentage ≥ than 0,1%.

12.6. Endocrine disrupting properties

Based on the available data, the product does not contain substances listed in the main European lists of potential or suspected endocrine disruptors with environmental effects under evaluation.

12.7. Other adverse effects

Information not available

SECTION 13. Disposal considerations

13.1. Waste treatment methods



| Reuse, when possible. Product residues should be considered special hazardous waste. The hazard level of waste containing this product should be evaluated according to applicable regulations. Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations. CONTAMINATED PACKAGING Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations. |
|--|
| SECTION 14. Transport information |
| |
| The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations. |
| 14.1. UN number or ID number |
| not applicable |
| |
| 14.2. UN proper shipping name |
| not applicable |
| 14.3. Transport hazard class(es) |
| not applicable |
| 14.4. Packing group |
| not applicable |
| 14.5. Environmental hazards |
| not applicable |
| 14.6. Special precautions for user |
| not applicable |



14.7. Maritime transport in bulk according to IMO instruments

Information not relevant

SECTION 15. Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Seveso Category - Directive 2012/18/EU: None

Restrictions relating to the product or contained substances pursuant to Annex XVII to EC Regulation 1907/2006

Product

Point 3

Contained substance

Point 75

Regulation (EU) 2019/1148 - on the marketing and use of explosives precursors

not applicable

Substances in Candidate List (Art. 59 REACH)

On the basis of available data, the product does not contain any SVHC in percentage ≥ than 0,1%.

Substances subject to authorisation (Annex XIV REACH)

None

Substances subject to exportation reporting pursuant to Regulation (EU) 649/2012:

None

Substances subject to the Rotterdam Convention:

None

Substances subject to the Stockholm Convention:

None

Healthcare controls

Workers exposed to this chemical agent must not undergo health checks, provided that available risk-assessment data prove that the risks related to the workers' health and safety are modest and that the 98/24/EC directive is respected.

15.2. Chemical safety assessment



Revision nr. 1

Dated 02/02/2024
First compilation
Printed on 02/02/2024

Style Oltre

Page n. 13/14

A chemical safety assessment has been performed for the following contained substances

REACTION MASS OF: BIS (1,2,2,6,6-Pentamethyl-4-Piperidyl) Sebacate and Methyl 1,2,2,6,6-Pentamethyl-4-Piperidyl Sebacate

SECTION 16. Other information

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

Repr. 2 Reproductive toxicity, category 2

Acute Tox. 4 Acute toxicity, category 4

Eye Dam. 1 Serious eye damage, category 1

Skin Irrit. 2 Skin irritation, category 2
Skin Sens. 1A Skin sensitization, category 1A

Aquatic Acute 1 Hazardous to the aquatic environment, acute toxicity, category 1

Aquatic Chronic 1 Hazardous to the aquatic environment, chronic toxicity, category 1

Aquatic Chronic 2 Hazardous to the aquatic environment, chronic toxicity, category 2

H361f Suspected of damaging fertility.

H302 Harmful if swallowed.

H318 Causes serious eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H400 Very toxic to aquatic life.


H410 Very toxic to aquatic life with long lasting effects.H411 Toxic to aquatic life with long lasting effects.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not

breathe spray or mist.

LEGEND:

- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- ATE: Acute Toxicity Estimate
- CAS: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CE: Identifier in ESIS (European archive of existing substances)
- CLP: Regulation (EC) 1272/2008
- DNEL: Derived No Effect Level
- EmS: Emergency Schedule
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- INDEX: Identifier in Annex VI of CLP
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PBT: Persistent bioaccumulative and toxic as REACH Regulation
- PEC: Predicted environmental Concentration
- PEL: Predicted exposure level
- PNEC: Predicted no effect concentration
- REACH: Regulation (EC) 1907/2006
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.



Revision nr. 1 Dated 02/02/2024 First compilation Printed on 02/02/2024

Style Oltre

Page n. 14/14

- TWA: Time-weighted average exposure limit
- TWA STEL: Short-term exposure limit
- VOC: Volatile organic Compounds
- vPvB: Very Persistent and very Bioaccumulative as for REACH Regulation
- WGK: Water hazard classes (German).

GENERAL BIBLIOGRAPHY

- 1. Regulation (EC) 1907/2006 (REACH) of the European Parliament
- 2. Regulation (EC) 1272/2008 (CLP) of the European Parliament
- 3. Regulation (EU) 2020/878 (II Annex of REACH Regulation)
 4. Regulation (EC) 790/2009 (I Atp. CLP) of the European Parliament
- 5. Regulation (EU) 286/2011 (II Atp. CLP) of the European Parliament
- 6. Regulation (EU) 618/2012 (III Atp. CLP) of the European Parliament
- 7. Regulation (EU) 487/2013 (IV Atp. CLP) of the European Parliament
- 8. Regulation (EU) 944/2013 (V Atp. CLP) of the European Parliament
- 9. Regulation (EU) 605/2014 (VI Atp. CLP) of the European Parliament
- 10. Regulation (EÚ) 2015/1221 (VII Atp. CLP) of the European Parliament
- 11. Regulation (EU) 2016/918 (VIII Atp. CLP) of the European Parliament
- 12. Regulation (EU) 2016/1179 (IX Atp. CLP)
- 13. Regulation (EU) 2017/776 (X Atp. CLP)
- 14. Regulation (EU) 2018/669 (XI Atp. CLP) 15. Regulation (EU) 2019/521 (XII Atp. CLP)
- 16. Delegated Regulation (UE) 2018/1480 (XIII Atp. CLP)
- 17. Regulation (EU) 2019/1148
- 18. Delegated Regulation (UE) 2020/217 (XIV Atp. CLP)
- 19. Delegated Regulation (UE) 2020/1182 (XV Atp. CLP)
- 20. Delegated Regulation (UE) 2021/643 (XVI Atp. CLP)
- 21. Delegated Regulation (UE) 2021/849 (XVII Atp. CLP)
- 22. Delegated Regulation (UE) 2022/692 (XVIII Atp. CLP)
- The Merck Index. 10th Edition
- Handling Chemical Safety
- INRS Fiche Toxicologique (toxicological sheet)
- Patty Industrial Hygiene and Toxicology
- N.I. Sax Dangerous properties of Industrial Materials-7, 1989 Edition
- IFA GESTIS website
- ECHA website
- Database of SDS models for chemicals Ministry of Health and ISS (Istituto Superiore di Sanità) Italy

Note for users:

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses. Provide appointed staff with adequate training on how to use chemical products.

CALCULATION METHODS FOR CLASSIFICATION

Chemical and physical hazards: Product classification derives from criteria established by the CLP Regulation, Annex I, Part 2. The data for evaluation of chemical-physical properties are reported in section 9.

Health hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 3, unless determined otherwise in Section 11.

Environmental hazards: Product classification is based on calculation methods as per Annex I of CLP, Part 4, unless determined otherwise in Section 12.